



700 LX Series MHFID Analyzer



- New Electronics
- User-Friendly Operation
- New, More Powerful Operating System
- Proven Analytical Components
- Remote Emulation/Control Software

Features

- Measures From Low 30 ppm up to 3% Full Scale as Methane
- Measures Methane Only or Total Hydrocarbons
- Auto Calibration and Ranging
- Fast Response Time
- Electronic Flow Control
- Temperature Stabilized Detector
- Automatic Fuel/Air Shut-off
- Comprehensive Diagnostics
- Output Options: Voltage, Current, RS-232, TCP/IP, MODBUS
- CE Mark and ETL Listed—Conforms to UL STD 61010-1, Certified to CAN/CSA C22.2 STD No. 610610.1
- Meets 1065 Requirements

Applications

- Combustion Efficiency
- Process Gas Analysis
- Fuel Cell Analysis
- Turbine/Generator Feedback Control
- Personnel Safety
- Vehicle Emissions

Options

- Internal Sample Pump
- Internal Solenoid Valves
- 19 Inch Rack Mount Slides

California Analytical Instruments

1312 West Grove Avenue, Orange, CA 92865 • Phone: 714-974-5560 • Fax: 714-921-2531
www.gasanalyzers.com



700 LX Series MHFID Analyzer

Method of Operation

The California Analytical Instruments' 700LX Series HFID Analyzer is designed to continuously measure the total concentration of hydrocarbons within a gaseous sample. The analyzer exhibits superior sensitivity and response time. The Analyzer utilizes the principle of Flame Ionization Detection (FID) to determine the total hydrocarbons within a gaseous sample. The HFID analyzer has a heated oven (191°C) which contains a burner and an optional heated pump. The small flame of the burner is elevated and sustained by the regulated flows of air and either pure hydrogen or a 40/60 mixture of hydrogen and (helium or nitrogen).

The split ring detector contains 2 electrodes. One electrode is negatively polarized using a precision power supply and the other electrode, known as the "collector" is connected to a high impedance, low noise electronic amplifier. The two electrodes establish an electrostatic field. When a gaseous sample is introduced to the burner, it is ionized in the flame and the electrostatic field causes the charged particles (ions) to migrate to their respective electrodes. The migration creates a small current between the electrodes. This current is measured by the precision electrometer amplifier and is directly proportional to the hydrocarbon concentration of the sample.

Specifications

Detector: Flame Ionization Detection
THC Ranges: Four User Definable ranges from 0-30 to 30,000 ppm as Methane or 0-10 to 10,000 ppm as Propane
(Contact Factory for Lower Ranges)
Non Methane Hydrocarbons: Calculated
Response Time: 90% Full Scale in 3 Seconds
Resolution Detection Limit: 10 ppb Carbon
Repeatability: Better than 0.5% of Full Scale
Linearity: Better than 1% of Full Scale
Accuracy: Better than 1% Full Scale
Precision: Better than 0.5% Full Scale
Noise: Less than 1% of Full Scale
Zero & Span Drift: Less than 1% of Full Scale per 24 Hours
Zero & Span Adjustment: Via front panel, TCP/IP, RS-232 or Digital Input
O₂ Effect: Less than 2% with H₂ / He Fuel
CH₄ Effect: Less than 1.2%
Flow Control: Electronic Proportional Pressure Controller
Sample Flow Rate: Typically 1.5 to 2.5 LPM
(Consult factory for other flow rates)
Fuel Requirements: 40% H₂ 60% He (124CC/min) or 100% H₂ (60cc/min) Specify at time of order
Fuel Inlet Pressure: 25 psig
Air Requirements: Less than 1ppm Carbon purified or Synthetic air (300cc/min for H₂/He; 400 cc/min for H₂)

Air Inlet Pressure: 25 psig
Fuel & Air Control: Electronic Proportional Pressure Controller
Readout: As ppm CH₄ or C₃H₈
Standard Outputs: Voltage, Current, RS-232 AK Protocol, TCP/IP MODBUS and AK Protocol
Assignable Contact Alarms and Statuses: 15 assignable contact closures
Digital Diagnostics: Temperature, Pressure, EPC Volt %, and Flow
Special Features: Auto Ranging, Auto Calibration
Display: 3" x 5" LED LCD
Sample Temperature: Up to 191°C, Non-condensing
Oven Temperature: 191°C
Ambient Temperature: 5 to 40°C
Ambient Humidity: Less than 90% RH (Non-condensing)
Warm-Up Time: 1 Hour (Typical)
Fittings: 1/4 Inch Tube
Power Requirements: 115/230 (±10%) VAC; 50/60 Hz, 750 Watts max.
Dimensions: 5¼ H x 19 W x 23 D (Inches)
Weight: 50 lbs.

Specifications subject to change without notice.

California Analytical Instruments

1312 West Grove Avenue, Orange, CA 92865 • Phone: 714-974-5560 • Fax: 714-921-2531
www.gasanalyzers.com